



EUCOLASTIC PRIMER

URETHANE SEALANT PRIMER

EUCLID CHEMICAL

JOINT SEALANTS

EUCOLASTIC PRIMER

MASTER FORMAT #: 00 00 00

DESCRIPTION

EUCOLASTIC PRIMER is a single-component, fast drying liquid primer that prepares non-porous surfaces for the application of Eucolastic 1NS and Eucolastic 1SL. **EUCOLASTIC PRIMER** imparts a surface finish which is very receptive to urethane sealants.

PRIMARY APPLICATIONS

- To prepare surface for the adhesion of urethane sealants
- Assures a water resistant bond on porous and non-porous substrates

FEATURES/BENEFITS

- Provides primer base for adhesion of Eucolastic sealants
- Increases adhesion for use in immersion situations
- Seals porous surfaces increasing water tightness

TECHNICAL INFORMATION

Typical Engineering Data

EUCOLASTIC PRIMER will dry in 30 to 45 minutes @ 21°C. Primer must be completely dry before installation of a Eucolastic sealant. If the EUCOLASTIC PRIMER becomes hard and glossy, the surface must be cleaned with solvent and reprimed.

Appearance: EUCOLASTIC PRIMER is a clear, one component liquid with a slight amber color.

PACKAGING/YIELD

EUCOLASTIC PRIMER is available in 0.95L units

SHELF LIFE

1 year in original, unopened container

COVERAGE RATES

Estimated coverage is 193 linear m/L per 13 mm depth of double faced joint.

INSTRUCTIONS FOR USE

Surface Preparation: New concrete must be a minimum of 28 days old. The joint must be clean and sound. All oil, dirt, debris, paint and any other material that could be a bond breaker must be removed. The final step in cleaning should be the complete removal of all residue with a vacuum cleaner or by pressure washing. All joint facings must be dry and have an open surface texture with all curing compounds and sealers removed.

Application: EUCOLASTIC PRIMER should be applied liberally with a clean brush or roller, but do not allow the product to puddle or pond. Use with adequate ventilation.

COVERAGE RATES

Tools, equipment and general clean-up can be done with thinners or acetone.

PRECAUTIONS/LIMITATIONS

- Keep containers sealed until ready to use.
- Opened containers have limited shelf life (less than 1 month).
- This product is amber in color and is noticeable on some surfaces. Care must be taken to apply only to areas that will be covered by final product.
- In all cases, consult the Safety Data Sheet before use.

Rev: 30/03/17

DISCLAIMER: Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request. Any suggested practices or installation specifications for the composite system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete SA (Pty) Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete Asia Sdn Bhd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.