

Ivory 312

Road Stud Adhesive

PRODUCT DATA SHEET

Uses

An epoxy tar adhesive used for fixing “cats-eyes” onto road surfaces, creating rumble strips, bonding concrete kerb stones to asphalt surface and other non structural applications.

Advantages

- Good weather resistance.
- Rapid cure
- Convenient mix ratio
- Good chemical resistance
- Resists attack by petroleum products.
- Can cure on damp surfaces

Preparation

All surfaces to be free of dust, road dirt and oil.

Application

Using volumes strictly in accordance with the given mixing ratio thoroughly mix the two components on a flat piece of wood or board with a putty knife or spatula.

- Apply the mixed material with a putty knife or pour into the required hole.
- If the mixed material is not used within 25 minutes of mixing, it will become unusable.
- Clean equipment immediately after use with *Ivory Water Soluble Brush Cleaner*.

Health & Safety

Some of the components of this product may be hazardous during mixing and application. Please consult the relevant Health & Safety Data Sheet available from Flowcrete on request and sent with each delivery.

Important Note

Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

Properties

No of components:	2
Colour:	Charcoal
Mixing Ratio by volume:	2:1
Pot life (250ml @ 25°C):	25 - 30 minutes
Cure Time:	
Practical:	2 hours
Full:	12 hours
Application Temperature:	Min 10°C Max 35°C
Cleaner:	W.S.B.C.
Thinners:	Do not thin
Shelf Life:	12 months