

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME REFERENCE 38/43 EPOXY

MSDS REVISION NUMBER 1

MANUFACTURER Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY

Bisphenol A type epoxy mixture

UN NUMBER 1866

PREPARED January 2013

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS 1. Bispenol A type epoxy

2. Xylene

R - PHRASES R 21/22/36/38/52/53

S - PHRASES S 1/2/26/28/36/37/39/45/61



SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY 2 - Moderate

HEALTH EFFECTS - EYES Severe eye irritant.

HEALTH EFFECTS - SKIN Severe skin irritant.

May cause skin sensitisation.

HEALTH EFFECTS - INGESTION Harmful if swallowed.

HEALTH EFFECTS - INHALATION Severe respiratory tract irritant.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Hold eye lids apart and immediately flush with plenty of

water for at least 15 minutes. Seek medical attention

immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water. Remove

contaminated clothing and shoes. Seek medical attention if

irritation persists.

INGESTION Immediately give plenty of water. Rinse mouth thoroughly

with water. Do not induce vomiting. Seek medical

attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is laboured,

give assisted respiration. Seek medical attention

immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING 2 - Moderate

PERSONAL PROTECTIVE EQUIPMENT Self-contained breathing apparatus and protective suit.

EXTINGUISHING MEDIA Water spray jet

Carbon dioxide

Foam

Dry powder

SPECIAL FIRE FIGHTING PROCEDURE

Use water to keep exposed containers cool. If a leak or

spill has not ignited, use water spray to disperse the vapours. Prevent runoff from fire control or dilution from

entering streams, sewers, or drinking water supply.



SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONS Contain or dyke the entire perimeter of the contaminated

area. Ensure that the spilled material does not enter any

drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the contained

spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers. Store away from all ignition sources. Avoid

sparking conditions. Ground all transfer equipment.

HANDLING Avoid contact with skin and eyes. Do not ingest or inhale.

When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide readily

accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots. Provide

readily accessible safety showers.

RESPIRATORY PROTECTIONUse in a well ventilated area. Wear suitable breathing

apparatus when there is inadequate ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe the

rules of hygiene.



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM Viscous liquid **COLOUR** Pigmented **ODOUR** Solvent N/A pН **BOILING POINT** No data MELTING POINT No data **FLASH POINT** $26^{\circ}C$ **FLAMMABILITY** 2 - Moderate VAPOUR PRESSURE No data

SOLUBILITY IN WATERNot soluble in water

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Heat, sparks, flame and build up of static electricity.

INCOMPATIBLE MATERIALS Strong oxidising substances

Active metals

HAZARDOUS DECOMPOSITION PRODUCTS

Burning produces obnoxious and toxic fumes.

SECTION 11 - TOXICOLOGICAL PROPERTIES

ACUTE ORAL TOXICITY (LD50, RAT) No data

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LD50, RAT) No data

EYE AND SKIN CONTACT Severe eye and skin irritant. Repeated exposure may cause

skin sensitisation.

CARCINOGENICITY Not a known carcinogen.

SECTION 12 - ECOLOGICAL INFORMATION

Material is expected to cause long term adverse effects in the aquatic environment.

This product is not readily biodegradable.



SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL Use a reputable waste disposal contractor. Waste disposal

measures must comply with all Local and National By-

laws.

SECTION 14 - TRANSPORT INFORMATION

UN NUMBER 1866

IMO SHIPPING NAME Resin solution, Flammable, N.O.S.

IMO CLASS AND DANGER GROUP Class 3, Danger Group III

IMO SUBSIDIARY RISK(S) None

SECTION 15 - REGULATORY INFORMATION

R 21 / 22 - Harmful in contact with skin and if swallowed. RISK (R) PHRASES

R 36 / 38 - Irritating to eyes and skin.

R 43 - May cause sensitisation by skin contact.

R 52 / 53 - Harmful to aquatic organisms, may cause long

term adverse effects in the aquatic environment.

SAFETY (S) PHRASES S 1 / 2 - Keep locked up and out of reach of children.

S 26 - In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S 28 - After contact with skin, wash immediately with

plenty of water and soap.

S 36 / 37 / 39 - Wear suitable protective clothing, gloves

and eye/face protection.

S 45 - In case of accident or if you feel unwell, seek

medical advice immediately.

S61 - Avoid release to the environment. Refer to special

instruction / material safety data sheet.



SECTION 16 - OTHER INFORMATION	
Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always se medical advice.	ek
All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted error of omission or the consequences thereof.	or

Flowcrete SA (Pty) Ltd is an RPM Company