

## **MATERIAL SAFETY DATA SHEET**

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION** 

**PRODUCT NAME IVORY 319 HI BOND SS ACTIVATOR** 

High performance impact modified epoxy adhesive.

**MSDS REVISION NUMBER** 1

**MANUFACTURER** Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

**TELEPHONE NUMBER** (031) 461 3411

**EMERGENCY TELEPHONE NUMBER(S) Rob Weyers** 

(031) 461 3411

**SYNONYMS** None

**CHEMICAL FAMILY** Modified polyamide

**UN NUMBER** 3082

**HAZARDOUS COMPONENTS** 

**PREPARED** 05 August 2012

**SECTION 2 - COMPOSITION** 

1. 30 - 60 %Triethylenetetramine

30 - 60 %Benzyl alcohol

**R-PHRASES** R 36 / 38 / 43 / 51 / 53 S - PHRASES S 26 / 28 / 36 / 37 / 61



OFOTION C. HATADDO IDENTIFICATION

**SECTION 3 - HAZARDS IDENTIFICATION** 

FLAMMABILITY 4 - Minimal

**HEALTH EFFECTS - EYES** Eye irritant.

**HEALTH EFFECTS - SKIN** Skin irritant.

May cause skin sensitisation.

**HEALTH EFFECTS - INGESTION** Harmful if swallowed.

**HEALTH EFFECTS - INHALATION** Respiratory irritant.

\_\_\_\_\_

**SECTION 4 - FIRST AID MEASURES** 

**EYE CONTACT**Hold eye lids apart and immediately flush with plenty

of water for at least 15 minutes. Seek medical

attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

**INGESTION** Rinse mouth thoroughly with water. Do not induce

vomiting. Seek medical attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek medical

attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

-----

FIRE RATING 4 - Minimal

EXTINGUISHING MEDIA Dry powder

Carbon dioxide Water spray

**REACTIVITY** 4 - Minimal



**SECTION 6 - ACCIDENTAL RELEASE MEASURES** 

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONS

Contain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

------

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

**HANDLING** Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke

------

\_\_\_\_\_

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

**EYE PROTECTION** Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

**SKIN PROTECTION** Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTION No respiratory protection is required under normal

conditions. Wear suitable breathing apparatus when

there is inadequate ventilation.

**INGESTION PROTECTION** Wash before eating, drinking or smoking. Observe

the rules of hygiene.



## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

-----

PHYSICAL FORM Paste **COLOUR** Amber **ODOUR** Ammoniacal Hq N/A > 180℃ **BOILING POINT MELTING POINT** No data **FLASH POINT** > 100°C 4 - Minimal FLAMMABILITY

VAPOUR PRESSURE No data SPECIFIC GRAVITY 0.93 – 0.99

**SOLUBILITY IN WATER** Practically insoluble in water.

**SECTION 10 - STABILITY AND REACTIVITY** 

\_\_\_\_\_\_

CHEMICAL STABILITY Stable

**CONDITIONS TO AVOID** Product is stable.

**INCOMPATIBLE MATERIALS**Mineral acids (H<sub>2</sub>SO<sub>4</sub>, H<sub>3</sub>PO<sub>4</sub>, etc.)

Alkalis (NaOH, KOH, etc.) Organic acids (CH<sub>3</sub>COOH, etc.)

Reducing agents Oxidising agents

Reactive metals (Na, Ca, Zn, etc.)

HAZARDOUS DECOMPOSITION PRODUCTS Carbon monoxide, carbon dioxide, ammonia,

irritating & toxic fumes at elevated temperatures.

**SECTION 11 - TOXICOLOGICAL PROPERTIES** 

------

ACUTE ORAL TOXICITY (LD50, RAT) > 2 000 mg / kg

ACUTE DERMAL TOXICITY (LD50, RABBIT) > 1000 mg / kg

ACUTE INHALATION TOXICITY (LD50, RAT) No data

EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure may cause

skin sensitisation.

**CARCINOGENICITY** Not a known carcinogen.



**SECTION 12 - ECOLOGICAL INFORMATION** Material is expected to cause long term adverse effects in the aquatic environment. **SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 3082 **IMO SHIPPING NAME** Environmentally hazardous substance, N.O.S. **IMO CLASS AND DANGER GROUP** Class 9, Danger Group III **IMO SUBSIDIARY RISK(S)** None **SECTION 15 - REGULATORY INFORMATION RISK (R) PHRASES** R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact. R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. **SAFETY (S) PHRASES** S 26 - In case of contact with eyes, rinse

advice.

aloves.

plenty of water and soap.

immediately with plenty of water and seek medical

S 28 - After contact with skin, wash immediately with

S 36 / 37 - Wear suitable protective clothing and

S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.



accepted for error of omission or the consequences thereof.

SECTION 16 - OTHER INFORMATION
Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomford always seek medical advice.
All information is given in good faith but without guarantee in respect of accuracy. No responsibility is

Flowcrete (SA) Pty Ltd (2003/029560/07)

176 Voortrekker Street Jacobs Durban 4052

Tel: +27 31 461 3411 Fax: +27 31 461 3475

47 Forge Road Spartan Kempton Park Johannesburg 1620

Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 086 583 8358

Email: southafrica@flowcrete.com

Flowcrete SA (Pty) Ltd is an RPM Company