

## **MATERIAL SAFETY DATA SHEET**

\_\_\_\_\_

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION** 

**PRODUCT NAME** AQUAPASTE

General purpose, structural epoxy adhesive

MSDS REVISION NUMBER

MANUFACTURER Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

**TELEPHONE NUMBER** (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY

Bisphenol A epoxy resin blend

UN NUMBER 3082

PREPARED January 2012

-----

**SECTION 2 - COMPOSITION** 

------

**HAZARDOUS COMPONENTS** 1. Bisphenol A type epoxy resin

2.  $C_{12} - C_{14}$  Aliphatic glycidyl ether

**R - PHRASES S - PHRASES**R 36 / 38 / 43 / 51 / 53

S 28 / 37 / 39 / 61



SECTION 3 - HAZARDS IDENTIFICATION

**SECTION 4 - FIRST AID MEASURES** 

FLAMMABILITY 4 - Minimal

**HEALTH EFFECTS - EYES** Eye irritant.

**HEALTH EFFECTS - SKIN** Skin irritant.

May cause skin sensitisation.

**HEALTH EFFECTS - INGESTION** Harmful if swallowed.

HEALTH EFFECTS - INHALATION Vapours are unlikely due to physical

properties.

-----

\_\_\_\_\_

**EYE CONTACT**Hold eye lids apart and immediately flush with

plenty of water for at least 15 minutes. Seek

medical attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and

water. Remove contaminated clothing and shoes. Seek medical attention if irritation

persists.

**INGESTION** Rinse mouth thoroughly with water. Do not

induce vomiting. Seek medical attention

immediately.

**INHALATION** Move to fresh air. If breathing has stopped

or is laboured, give assisted respiration.

Seek medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING 4 - Minimal

EXTINGUISHING MEDIA Foam

Dry powder Carbon dioxide Water spray jet

**REACTIVITY** 4 - Minimal



------

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves,

and eye protection.

**ENVIRONMENTAL PRECAUTIONS**Contain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or

ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National Bylaws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

SECTION 7 - HANDLING AND STORAGE

------

STORAGE Keep in cool, dry, ventilated storage and in

closed containers.

HANDLING Avoid contact with skin and eyes. Do not

ingest or inhale. When handling, do not eat,

drink or smoke.

------

**SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS** 

-----

**EYE PROTECTION** Wear chemical safety glasses or goggles.

Provide readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and

boots. Provide readily accessible safety

showers.

RESPIRATORY PROTECTION No respiratory protection is required under

normal conditions. Wear suitable breathing apparatus when there is inadequate

ventilation.



INGESTION PROTECTION Wash before eating, drinking or smoking.

Observe the rules of hygiene.

.....

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES** 

PHYSICAL FORM Paste **COLOUR** Off White **ODOUR** Faint epoxy pН N/A **BOILING POINT** > 200℃ **MELTING POINT** No data **FLASH POINT** > 100°C **FLAMMABILITY** 4 - Minimal

VAPOUR PRESSURE
No data
SPECIFIC GRAVITY
1.800

**SOLUBILITY IN WATER** Practically insoluble in water.

\_\_\_\_\_\_

**SECTION 10 - STABILITY AND REACTIVITY** 

\_\_\_\_\_

CHEMICAL STABILITY Stable

**CONDITIONS TO AVOID** Excessive heating over long periods of time

degrades the product causing discolouration.

INCOMPATIBLE MATERIALS Strong oxidising substances

Strong acids Strong alkalis Amines

**HAZARDOUS DECOMPOSITION PRODUCTS** In a fire, toxic fumes may be generated.

------

**SECTION 11 - TOXICOLOGICAL PROPERTIES** 

------

ACUTE ORAL TOXICITY (LD50, RAT) No data

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LD50, RAT) Vapours are unlikely due to physical

properties.

EYE AND SKIN CONTACT Eye and skin irritant. Repeated exposure may

cause skin sensitisation.

**CARCINOGENICITY** Not a known carcinogen.



SECTION 12 - ECOLOGICAL INFORMATION Material is expected to cause long term adverse effects in the aquatic environment. This product is not readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 3082 **IMO SHIPPING NAME** Environmentally hazardous substance, N.O.S. IMO CLASS AND DANGER GROUP Class 9, Danger Group III IMO SUBSIDIARY RISK(S) None SECTION 15 - REGULATORY INFORMATION **RISK (R) PHRASES** R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact. R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. **SAFETY (S) PHRASES** S 28 - After contact with skin, wash immediately with plenty of water and soap. S 37 / 39 - Wear suitable gloves and eye/face protection. S 61 - Avoid release to the environment. Refer to special instruction / material safety

data sheet.



accepted for error of omission or the consequences thereof.

SECTION 16 - OTHER INFORMATION	
Alert workers to this hazardous potential and ensure precautions are taken. discomfort always seek medical advice.	In cases of any
All information is given in good faith but without guarantee in respect of accuracy.	No responsibility is

Flowcrete (SA) Pty Ltd (2003/029560/07)

176 Voortrekker Street Jacobs Durban 4052

Tel: +27 31 461 3411 Fax: +27 31 461 3475

47 Forge Road Spartan Kempton Park Johannesburg 1620

Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 086 583 8358