

**PRODUCT NAME** 

# **MATERIAL SAFETY DATA SHEET**

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION** 

FLOWSEAL EPW EPOXY Water Based Epoxy Enamel

MSDS REVISION NUMBER 1

MANUFACTURER Flowcrete S.A. (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

**TELEPHONE NUMBER** (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY Epoxy resin

UN NUMBER 3082

PREPARED January 2016

**SECTION 2 - COMPOSITION** 

\_\_\_\_\_\_

HAZARDOUS COMPONENTS 1. Epoxy resin (average molecular

weight < 700)

2. Neodecanoic acid glycidyl ester

**R - PHRASES S - PHRASES**R 36 / 38 / 43 / 51 / 53

S - 24 / 26 / 28 / 37 / 39 / 61

\_\_\_\_\_\_\_



**SECTION 3 - HAZARDS IDENTIFICATION** 

**FLAMMABILITY** 4 - Minimal

**HEALTH EFFECTS - EYES** Eye irritant.

**HEALTH EFFECTS - SKIN** Skin irritant.

May cause skin sensitisation.

**HEALTH EFFECTS - INGESTION** Harmful if swallowed.

**HEALTH EFFECTS - INHALATION** Vapours are unlikely due to physical properties.

**SECTION 4 - FIRST AID MEASURES** 

**EYE CONTACT** Hold eye lids apart and immediately flush with

plenty of water for at least 15 minutes. Seek

medical attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

Rinse mouth thoroughly with water. Do not induce **INGESTION** 

vomiting. Seek medical attention immediately.

**INHALATION** Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek medical

attention immediately.

**SECTION 5 - FIRE FIGHTING MEASURES** 

**FIRE RATING** 4 - Minimal

**EXTINGUISHING MEDIA** Foam

Dry chemical powder Carbon dioxide Water spray or fog

Sand or earth (for small fires)

SPECIAL FIRE FIGHTING PROCEDURES Fire fighters should wear boots, gloves, long

sleeved overalls and self-contained breathing

apparatus.

**REACTIVITY** 4 – Minimal

Flowcrete SA (Pty) Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052

Tel: +27 31 461 3411 Fax: +27 31 461 3475 47 Forge Road Spartan Kempton Park Johannesburg 1619

Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 0865 83 8358 Email: southafrica@flowcrete.com

www.flowcretesa.co.za



## **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

**ENVIRONMENTAL PRECAUTIONS**Contain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder

immediately.

**SECTION 7 - HANDLING AND STORAGE** 

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

HANDLING Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

**SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS** 

**EYE PROTECTION** Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

**SKIN PROTECTION** Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTION No respiratory protection is required under normal

conditions. Wear suitable breathing apparatus

when there is inadequate ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe

the rules of hygiene.

\_\_\_\_\_

Flowcrete SA (Pty) Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1619
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490
Tel: +27 21 385 0653 Fax: 0865 83 8358

Email: southafrica@flowcrete.com

Flowseal EPW Epoxy - Page 3 of 5

www.flowcretesa.co.za



## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL FORM Mobile liquid

COLOUR Colourless – slight yellow

ODOUR Faint epoxy pH N/A

BOILING POINT

MELTING POINT

No data

No data

FLASH POINT

FLAMMABILITY

VAPOUR PRESSURE

No data

No data

No data

VISCOSITY 61 - 67 KU / FP

SPECIFIC GRAVITY 1.01

**SOLUBILITY IN WATER** Soluble in water.

### **SECTION 10 - STABILITY AND REACTIVITY**

-----

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID None. Stable under recommended storage and

handling conditions.

INCOMPATIBLE MATERIALS Strong oxidising substances

#### **SECTION 11 - TOXICOLOGICAL PROPERTIES**

------

ACUTE ORAL TOXICITY (LD50, RAT) No data

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LC50, RAT) Vapours are unlikely due to physical properties.

**EYE AND SKIN CONTACT** Eye and skin irritant. Repeated exposure may cause

skin sensitisation.

**CARCINOGENICITY** Not a known carcinogen.

#### ------

#### **SECTION 12 - ECOLOGICAL INFORMATION**

Material is expected to cause short term adverse effects in the aquatic environment.

This product is not readily biodegradable.

Flavorate SA (Dt.) Ltd (2002 (020540 (07)

Flowcrete SA (Pty) Ltd (2003/029560/07) 176 Voortrekker Street Jacobs Durban 4052 Tel: +27 31 461 3411 Fax: +27 31 461 3475 47 Forge Road Spartan Kempton Park Johannesburg 1619 Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein Cape Town 7490

Tel: +27 21 385 0653 Fax: 0865 83 8358

Email: southafrica@flowcrete.com





**SECTION 13 - DISPOSAL CONSIDERATIONS** 

WASTE DISPOSAL

Use a reputable waste disposal contractor. Waste

disposal measures must comply with all Local and

National By-laws.

**SECTION 14 - TRANSPORT INFORMATION** 

-----

.....

UN NUMBER 3082

IMO SHIPPING NAME Environmentally hazardous substance, Liquid,

N.O.S.

IMO CLASS AND DANGER GROUP Class 9, Danger Group III

IMO SUBSIDIARY RISK(S) None

SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES R 36 / 38 – Irritating to eyes and skin.

R 43 – May cause sensitisation by skin contact.

R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic

environment.

SAFETY (S) PHRASES S 24 – Avoid contact with skin.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S 28 – After contact with skin, wash immediately

with plenty of water and soap.

S 37 / 39 - Wear suitable gloves and eye/face

protection.

S61 - Avoid release to the environment. Refer to

special instruction / material safety data sheet.

**SECTION 16 - OTHER INFORMATION** 

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without grouped in general of accuracy. No generalisity is

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete SA (Pty) Ltd (2003/029560/07) 176 Voortrekker Street Jacobs Durban 4052 Tel: +27 31 461 3411 Fax: +27 31 461 3475 47 Forge Road Spartan Kempton Park Johannesburg 1619 Tel: +27 11 394 1980 Fax: +27 11 394 3003

Flowseal EPW Epoxy - Page 5 of 5

www.flowcretesa.co.za