

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME IVORY 366 EPOXY

MSDS REVISION NUMBER 1

MANUFACTURER Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyer

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY

Bisphenol A type epoxy mixture

UN NUMBER 1866

PREPARED January 2011

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS

1. Bispenol A type epoxy

Toluene
 Butanol

R - PHRASES R 21 / 22 / 36 / 38 / 52 / 53

S - PHRASES S 1 / 2 / 26 / 28 / 36 / 37 / 39 / 45 / 61



SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY 2 - Moderate

HEALTH EFFECTS - EYES Severe eye irritant.

HEALTH EFFECTS - SKIN Severe skin irritant.

May cause skin sensitisation.

HEALTH EFFECTS - INGESTIONHarmful if swallowed.

HEALTH EFFECTS - INHALATION Severe respiratory tract irritant.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Hold eye lids apart and immediately flush with plenty

of water for at least 15 minutes. Seek medical

attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

INGESTION Immediately give plenty of water. Rinse mouth

thoroughly with water. Do not induce vomiting. Seek

medical attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek medical

attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE RATING 2 - Moderate

PERSONAL PROTECTIVE EQUIPMENT

Self-contained breathing apparatus and protective

suit.

EXTINGUISHING MEDIA Water spray jet

Carbon dioxide

Foam Dry powder

SPECIAL FIRE FIGHTING PROCEDURE

Use water to keep exposed containers cool. If a leak

or spill has not ignited, use water spray to disperse the vapours. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water

supply.



CECTION C. ACCIDENTAL DELEACE MEACUREC

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONSContain or dyke the entire perimeter of the

contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE Working from the outer circumference of the

contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the inhouse capabilities, call a spill responder immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage ar

Keep in cool, dry, ventilated storage and in closed containers. Store away from all ignition sources.

Avoid sparking conditions. Ground all transfer

equipment.

HANDLING Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTIONUse in a well ventilated area. Wear suitable breathing

apparatus when there is inadequate ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe

the rules of hygiene.



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM Mobile liquid

COLOUR

ODOUR

Solvent

PH

N/A

BOILING POINT

No data

MELTING POINT

No data

FLASH POINT

26 °C

FLAMMABILITY 2 - Moderate VAPOUR PRESSURE No data

VISCOSITY 61 - 67 KU / FP

SPECIFIC GRAVITY 1.28

SOLUBILITY IN WATER Not soluble in water

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOIDHeat, sparks, flame and build up of static electricity.

INCOMPATIBLE MATERIALS Strong oxidising substances

Active metals

HAZARDOUS DECOMPOSITION PRODUCTSBurning produces obnoxious and toxic fumes.

SECTION 11 - TOXICOLOGICAL PROPERTIES

ACUTE ORAL TOXICITY (LD50, RAT) No data

ACUTE DERMAL TOXICITY (LD50, RABBIT) No data

ACUTE INHALATION TOXICITY (LD50, RAT) No data

EYE AND SKIN CONTACT Severe eye and skin irritant. Repeated exposure may

cause skin sensitisation.

CARCINOGENICITY Not a known carcinogen.



SAFETY (S) PHRASES

SECTION 12 - ECOLOGICAL INFORMATION Material is expected to cause long term adverse effects in the aquatic environment. This product is not readily biodegradable. **SECTION 13 - DISPOSAL CONSIDERATIONS WASTE DISPOSAL** Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws. **SECTION 14 - TRANSPORT INFORMATION UN NUMBER** 1866 **IMO SHIPPING NAME** Resin solution, Flammable, N.O.S. IMO CLASS AND DANGER GROUP Class 3, Danger Group III **IMO SUBSIDIARY RISK(S)** None **SECTION 15 - REGULATORY INFORMATION** R 21 / 22 - Harmful in contact with skin and if **RISK (R) PHRASES** R 36 / 38 - Irritating to eyes and skin. R 43 - May cause sensitisation by skin contact. R 52 / 53 - Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

S 1 / 2 - Keep locked up and out of reach of children.

S 26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 28 - After contact with skin, wash immediately with plenty of water and soap.

S 36 / 37 / 39 - Wear suitable protective clothing, gloves and eye/face protection.

S 45 - In case of accident or if you feel unwell, seek medical advice immediately.

S 61 - Avoid release to the environment. Refer to special instruction / material safety data sheet.



SECTION 16 - OTHER INFORMATION
Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.
All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete SA (Pty) Ltd is an RPM Company