

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME RUSTIK UV BINDER BASE

MSDS REVISION NUMBER

MANUFACTURER Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(0310 461 3411

SYNONYMS None

CHEMICAL FAMILY Hydroxy functional acrylic mixture

UN NUMBER 1866

PREPARED January 2014

SECTION 2 - COMPOSITION

Flowcrete SA (Pty) Ltd is an RPM Company

HAZARDOUS COMPONENTS 1. Xylene

Methyl propasol acetate

R - PHRASESR 10 / 20 / 21 / 22 / 36 / 38 / 43 / 52 / 53 **S - PHRASES**R 10 / 20 / 21 / 22 / 36 / 37 / 39 / 45 / 51 / 61

Rustik UV Binder Base - Page 1 of 6



CECTION 2 HAZADDO IDENTIFICATION

SECTION 3 - HAZARDS IDENTIFICATION

FLAMMABILITY 1 - Serious

HEALTH EFFECTS - EYESSevere eye irritant.

HEALTH EFFECTS - SKIN Severe skin irritant.

May cause skin sensitisation.

HEALTH EFFECTS - INGESTIONHarmful if swallowed.

HEALTH EFFECTS - INHALATION Severe respiratory tract irritant.

.....

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Hold eye lids apart and immediately flush with

plenty of water for at least 15 minutes. Seek

medical attention immediately.

SKIN CONTACT Rinse thoroughly with plenty of soap and water.

Remove contaminated clothing and shoes. Seek

medical attention if irritation persists.

INGESTION Rinse mouth thoroughly with water. Do not induce

vomiting. Seek medical attention immediately.

INHALATION Move to fresh air. If breathing has stopped or is

laboured, give assisted respiration. Seek medical

attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flowcrete SA (Pty) Ltd is an RPM Company

FIRE RATING 1 - Serious

PERSONAL PROTECTIVE EQUIPMENT Self-contained breathing apparatus and protective

suit.

EXTINGUISHING MEDIA Carbon dioxide

Foam Dry powder

Rustik UV Binder Base - Page 2 of 6

Flowcrete SA (Pty) Ltd (2003/029560/07)
176 Voortrekker Street Jacobs 4052 Durban
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park 1619 Johannesburg
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein 7490 Cape Town
Tel: 0861 00 7703 | +27 21 385 0653 Fax: 0865 83 8358
Email: southafrica@flowcrete.com



SPECIAL FIRE FIGHTING PROCEDURE

Use water to keep exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapours. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear long sleeved clothing, boots, gloves, and eye protection.

ENVIRONMENTAL PRECAUTIONS

Contain or dyke the entire perimeter of the contaminated area. Ensure that the spilled material does not enter any drains, surface or ground water.

SPILL CLEAN-UP PROCEDURE

Working from the outer circumference of the contained spill area, absorb the product with sand or sawdust. Collect and place the contaminated materials in an approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the in-house capabilities, call a spill responder immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE

Keep in cool, dry, ventilated storage and in closed containers. Store away from all ignition sources. Avoid sparking conditions. Ground all transfer equipment.

HANDLING

Flowcrete SA (Pty) Ltd is an RPM Company

Avoid contact with skin and eyes. Do not ingest or inhale. When handling, do not eat, drink or smoke. Ensure adequate ventilation or exhaust ventilation in the working area. Exhaust ventilation is required if the product is sprayed.

Rustik UV Binder Base - Page 3 of 6



SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

SECTION 0 - 1 ENGONAL PROTECTION / EXPOSORE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTIONUse in a well ventilated area. Wear suitable

breathing apparatus when there is inadequate

ventilation.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe

the rules of hygiene.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

.....

PHYSICAL FORM
COLOUR
ODOUR
Mobile liquid
Pigmented
Smell of solvent

pHN/ABOILING POINTNo dataMELTING POINTNo dataFLASH POINT< 23 ℃</td>FLAMMABILITY1 - SeriousVAPOUR PRESSURENo dataSPECIFIC GRAVITY1.20

SOLUBILITY IN WATER Not soluble in water

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Heat, sparks, flame and build up of static electricity.

HAZARDOUS DECOMPOSITION PRODUCTS

No hazardous decomposition products expected when stored and handled correctly.

When exposed to high temperatures carbon monoxide, dioxide, smoke and oxides of nitrogen

may be produced.

Rustik UV Binder Base - Page 4 of 6

Flowcrete SA (Pty) Ltd (2003/029560/07)
176 Voortrekker Street Jacobs 4052 Durban
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park 1619 Johannesburg
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein 7490 Cape Town
Tel: 0861 00 7703 | +27 21 385 0653 Fax: 0865 83 8358
Email: southafrica@flowcrete.com

Flowcrete SA (Pty) Ltd is an RPM Company



SECTION 11 - TOXICOLOGICAL PROPERTIES	
ACUTE ORAL TOXICITY (LD50, RAT)	No data
ACUTE DERMAL TOXICITY (LD50, RABBIT)	No data
ACUTE INHALATION TOXICITY (LC50, RAT)	No data
EYE AND SKIN CONTACT	Severe eye and skin irritant. Repeated exposure may cause skin sensitisation.
SECTION 12 - ECOLOGICAL INFORMATION	
Material is expected to cause long term adverse eff	ects in the aquatic environment.
SECTION 13 - DISPOSAL CONSIDERATIONS	
WASTE DISPOSAL	Use a reputable waste disposal contractor. Waste disposal measures must comply with all Local and National By-laws.
SECTION 14 - TRANSPORT INFORMATION	
UN NUMBER	1866
IMO SHIPPING NAME	Resin solution, Flammable, N.O.S.
IMO CLASS AND DANGER GROUP	Class 3, Danger Group III
IMO SUBSIDIARY RISK(S)	None
SECTION 15 - REGULATORY INFORMATION	
RISK (R) PHRASES	R 10 - Flammable R 20 / 21 / 22 - Harmful by inhalation, in contact

with skin and if swallowed.

R 36 / 38 - Irritating to eyes and skin.

R 43 - May cause sensitisation by skin contact.

Flowcrete SA (Pty) Ltd (2003/029560/07) 176 Voortrekker Street Jacobs 4052 Durban Tel: +27 31 461 3411 Fax: +27 31 461 3475 47 Forge Road Spartan Kempton Park 1619 Johannesburg Tel: +27 11 394 1980 Fax: +27 11 394 3003

Unit 5 55 Manhattan Street Boquinar Industrial Area Matroosfontein 7490 Cape Town Tel: 0861 00 7703 | +27 21 385 0653 Fax: 0865 83 8358

Email: southafrica@flowcrete.com Flowcrete SA (Pty) Ltd is an RPM Company Rustik UV Binder Base – Page 5 of 6



SAFETY (S) PHRASES

- R 52 / 53 Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.
- S 1 / 2 Keep locked up and out of reach of children.
- S 24 Avoid contact with skin.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 28 After contact with skin, wash immediately with plenty of water and soap.
- S 36 / 37 / 39 Wear suitable protective clothing, gloves and eye/face protection.
- S 45 In case of accident or if you feel unwell, seek medical advice immediately.
- S 51 Use only in well ventilated areas.
- S61 Avoid release to the environment. Refer to special instruction / material safety data sheet.

SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Rustic UV Binder Base - Page 6 of 6

Flowcrete SA (Pty) Ltd is an RPM Company