

Rustik UV (6mm)

A decorative UV stable stone carpet system containing natural stone aggregates.



Decorative:

Stone carpet system designed to bring the beauty of the outdoors inside.



Slip Resistant:

Positively textured profile to minimise the risk of slip and trip accidents.



Fast Installation:

Hand broadcast aggregates ensure large areas can be installed quickly.



Wear Resistant:

Excellent scratch and wear resistance to foot and tire traffic.



UV Resistant:

100% UV stable formulation. Prevents the floor from yellowing.



Natural Light



Natural Dark

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your regional Flowcrete office.

Technical Profile

SLIP RESISTANCE

BS 7976-2	Dry: 40	Wet: 36
-----------	---------	---------

ABRASION RESISTANCE

BS 8204-2	Class AR2 – Medium duty industrial and commercial
-----------	---

IMPACT RESISTANCE

ISO 6272	1kg weight > 1.8 metres 2kg weight > 1.5 metres
----------	--

TEMPERATURE RESISTANCE

Tolerant of sustained temperatures up to 50°C

COMPRESSIVE STRENGTH

BS 6319	50 N/mm ²
---------	----------------------

FLEXURAL STRENGTH

BS 6319	10 N/mm ²
---------	----------------------

BOND STRENGTH


> 1.5 MPa

TOXICITY

Taint free to sensitive foodstuffs

* These figures are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.

SPEED OF CURE	10°C	20°C	30°C
Light Traffic	36 hrs	24 hrs	24 hrs
Full Traffic	72 hrs	48 hrs	48 hrs
Full Chemical Cure	12 days	7 days	7 days



Model Specification

System	Rustik UV
Finish	Gloss
Thickness	6mm
Colour	See standard colour chart

Preparatory work and application in accordance with manufacturer's instructions.

Products Included in this System

Primer	Rustik UV Binder
Scatter	Rustic Stones
Binder	Rustik UV Binder
Topping	Rustic Stones
Sealer	Flowcoat UV Clear

Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/mm², and maintain a minimum tensile strength of 1.5 MPa, free from laitance, dust and other contamination. The substrate should have a moisture content of no more than 5%.

Installation Service

This installation should be carried out by an Approved Applicator. For details of our Approved Applicators, contact our regional office. Detailed application instructions are available upon request.

Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs and maintenance. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained application teams.

Focus on the Floorzone

Flowcrete is a market leader in specialist industrial and commercial flooring. Systems available include: floor screeds, surface damp proof membranes, decorative flooring, seamless terrazzo, car park deck coatings, tank lining systems ... to name just a few. Our objective is to satisfy your Floorzone needs.

Warranty

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard "Warranty, Terms and Conditions of Sale", copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages. Please review warranty in detail before installing the products.