

SAFE – T - 3

Cold Cleaning Solvent

SAFE-T-3 is a cold cleaning solvent of low toxicity, specially blended for the safe cleaning of electrical units. SAFE-T-3 combines the cleaning and solvent properties of aliphatic hydrocarbon and chlorinated solvents.

Uses

SAFE-T-3 is a powerful solvent which readily dissolves organic matter such as oils, grease, waxes and tar, but does not attack the underlying paint, varnish, insulations and metals. The evaporation rate has been retarded, enabling **SAFE-T-3** to be used undiluted by spray, immersion, brushing or wiping.

SAFE-T-3 does not burn, has no flash point and is non conducting.

Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

Flash point	-none at boiling point
MAC rating	-over 500 ppm
Colour	-clear
Dielectric constant	-0.30 @ 20 degrees C
Non conductor of electricity	
Evaporation rate	6½ times slower than carbon tetrachloride.

Important

- All electrical cleaning solvents should be used in well ventilated areas.
- Avoid prolonged contact with eyes, skin, clothing.
- Do not use near open flames.
- The cleaned component should be thoroughly dry before it is reconnected in a live electrical circuit.
- Use in well ventilated areas.
- When used in open or well ventilated areas, the use of respirators is not considered necessary.