

Ivosheen

Pure Acrylic Coating Based Paint

Description

Ivosheen is a finishing paint, formulated to give excellent durability for interior and exterior applications. Based on the highest grade pure acrylic emulsion *Ivosheen* has excellent ultra violet resistant properties ensuring extended life even under exacting environmental conditions.

Uses

Suitable for use on most surfaces provided that the correct surface preparation and primers are used. Highly recommended for use on the exterior walls of buildings, workshop walls, halls, stairwells, corridors, hospitals, bathrooms and ablution walls, fascia boards, asbestos down pipes.

Advantages

- Single pack
- No volatile solvents
- Excellent ultraviolet light resistance
Excellent hiding power
- Non yellowing and good stain resistance
Thermoplastic and will not embrittle
- Very low dirt retention and easy cleaning

Preparation

Ivory manufactures detergents, etchants, degreasers, de-rusters, sanitizers etc., for all preparation requirements. All surfaces to be clean, sound and dry. All existing paint surfaces to be thoroughly washed with detergent to remove any dirt. Stiff bristle or wire brushes used to remove flaking or peeling paint and oxidation products.

Priming

Concrete, Masonry, Plaster & Asbestos

1. Previously coated with good emulsion paints - clean with damp cloth and dry, no priming required.
2. Previously coated with solvent paints - lightly abrade with fine abrasive paper, clean with damp cloth and dry, no priming required.
3. Uncoated - clean with damp cloth, dry, apply one coat of *Ivoseal* at 6m²/ℓ.

Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20 °C and at 50% Relative Humidity.

N° of components:	1
Drying Time:	
Touch Dry	½ hour
Service	6 hours
Full Cure	7 days
Over Coating Time:	6 hours
Coverage:	± 10 - 12m ² /ℓ
Recommended N° of coats:	
Primer + 2 coats dependant on substrate	
d.f.t. @ 10m ² /ℓ:	40 microns.
Colours:	See colour chart
Equipment Cleaning:	Water

Galvanized Iron, Aluminum

1. Previously coated and sound - lightly abrade with fine abrasive paper, clean with damp cloth and dry, no priming required.
2. Coated but peeling - remove all paint, wash well with detergent, dry and apply one coat of *Ivocryl* straw primer at 7m²/ℓ.

Timber (Fascia Boards, Panelling etc)

Apply one coat of *Ivoseal* acrylic at 8m²/ℓ.

Application

Apply by brush, mohair roller or airless spray.

Specification

Prepare and prime surfaces and apply two coats *Ivosheen* all strictly in accordance with the manufacturers detailed instructions.

Important Note

Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.