



## Super Satin (Matt)

A two-component water-borne polyurethane formulated to provide an ultra-durable clear coating with a matt finish.



### Pot Life

Long pot life



### Easy to Clean

Good stain resistance. Excellent mar resistance.



### Chemical Resistance

Good resistance to spillages of most dilute solutions of acids and alkalis, aliphatic solvents, alcohols, grease and oil.

## Technical Profile

### NO. OF COMPONENTS

2

### MIX RATIO

9:1

### POT LIFE

2 Hours

### OVERCOAT TIME

6 Hours

### PRACTICAL CURE

12 Hours

### APPLY BY

Brush or mohair roller

### COVERAGE

8 to 10m<sup>2</sup>/litre/coat

### DFT PER COAT AT 8m<sup>2</sup>/LITRE

± 40 microns

### APPLICATION TEMPERATURE

10 to 30°C

### NUMBER OF COATS

2

### CLEANER

Water

### SHELF LIFE

12 Months

\* These figures are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.

### SPEED OF CURE

Touch Dry	3 Hours
Overcoat Time	6 Hours
Practical Cure	12 Hours

For applications falling outside of this temperature range, please contact your local Flowcrete Technical Department.

## Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/mm<sup>2</sup>, and maintain a minimum tensile strength of 1.5 MPa, free from laitance, dust and other contamination. The substrate should have a moisture content of no more than 5%.

## Installation Service

This installation should be carried out by an Approved Applicator. For details of our Approved Applicators, contact our regional office. Detailed application instructions are available upon request.

## Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

## Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs and maintenance. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained application teams.

## Focus on the Floorzone

Flowcrete is a market leader in specialist industrial and commercial flooring. Systems available include: floor screeds, surface damp proof membranes, decorative flooring, seamless terrazzo, car park deck coatings, tank lining systems ... to name just a few. Our objective is to satisfy your Floorzone needs.

## Warranty

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages. Please review warranty in detail before installing the products.