

IVORY 340/5/LV

Low Viscosity Solvent Free Penetrating Epoxy System

PRODUCT DATA SHEET

Description

A low viscosity, solvent free, penetrating epoxy system.

Uses

For the saturation and penetration of concrete surfaces and cracks to seal and strengthen.

Preparation

Surfaces to be clean, sound and dust free and have a maximum moisture content of 4%.

Application

- Thoroughly mix together only enough product which can be applied in 20 minutes at 25°C.
- Apply by brush or roller, applying successive coats wet on wet until no further absorption of epoxy occurs.
- Should over 18 hours lapse between the coating of the Ivory 340/5/LV and the top coat or finish coat the surface of the previous coating must be abraded with a medium grit abrasive paper and solvent wiped using epoxy thinners.

Health & Safety

Some of the components of this product may be hazardous during mixing and application. Please consult the relevant Health & Safety Data Sheet available from Flowcrete on request and sent with each delivery.

Important Note

Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

Properties

No of components:	2
Mixing Ratio:	2:1
Epoxy/Activator by volume	20 mins
Pot life (250m ^l @ 25°C):	Brush or roller
Apply by:	Depends on the density of the timber
Theoretical Coverage:	Wet on wet
Overcoat time:	Min 6 hours
Over coating time for top Coat or finish coat:	Max 18 hours
Colour:	Clear
Cleaner:	W.S.B.C.
Shelf life:	12 months