

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME IVORY 317 HI WEAR EPOXY

Abrasion resistant wearing compound

MANUFACTURER Flowcrete SA (Pty.) Ltd.

176 Voortrekker Street

Jacobs 4052

TELEPHONE NUMBER (031) 461 3411

EMERGENCY TELEPHONE NUMBER(S) Rob Weyers

(031) 461 3411

SYNONYMS None

CHEMICAL FAMILY Epoxy resin of Bisphenol A, epichlorohydrin type

UN NUMBER 3082

PREPARED 14 August 2012

SECTION 2 - COMPOSITION

HAZARDOUS COMPONENTS 1. Bisphenol A

R - PHRASES S - PHRASESR 36 / 38 / 43 / 51 / 53
S - 28 / 37 / 39 / 61



SECTION 3 - HAZARDS IDENTIFICATION FLAMMABILITY Minimal **HEALTH EFFECTS - EYES** Slight eye irritant. **HEALTH EFFECTS - SKIN** Mild skin irritant. May cause skin sensitisation. **HEALTH EFFECTS - INGESTION** Harmful if swallowed. **HEALTH EFFECTS - INHALATION** Vapours are unlikely due to physical properties. **SECTION 4 - FIRST AID MEASURES EYE CONTACT** Hold eye lids apart and immediately flush with plenty of water for at least 15 minutes. Seek medical attention immediately. **SKIN CONTACT** Rinse thoroughly with plenty of soap and water. Remove contaminated clothing and shoes. Seek medical attention if irritation persists. **INGESTION** Rinse mouth thoroughly with water. Do not induce vomiting. Seek medical attention immediately. **INHALATION** Move to fresh air. If breathing has stopped or is laboured, give assisted respiration. Seek medical attention immediately. **SECTION 5 - FIRE FIGHTING MEASURES FIRE RATING** Minimal **REACTIVITY** Minimal



SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear long sleeved clothing, boots, gloves, and eye

protection.

ENVIRONMENTAL PRECAUTIONSEnsure that the spilled material does not enter any

drains.

SPILL CLEAN-UP PROCEDURE Collect and place the contaminated materials in an

approved disposal container. Dispose of contaminants in accordance with the Local and National By-laws. Should the spill exceed the inhouse capabilities, call a spill responder immediately.

SECTION 7 - HANDLING AND STORAGE

STORAGE Keep in cool, dry, ventilated storage and in closed

containers.

HANDLING Avoid contact with skin and eyes. Do not ingest or

inhale. When handling, do not eat, drink or smoke.

SECTION 8 - PERSONAL PROTECTION / EXPOSURE CONTROLS

EYE PROTECTION Wear chemical safety glasses or goggles. Provide

readily accessible eye wash stations.

SKIN PROTECTION Wear long sleeved clothing, gloves, and boots.

Provide readily accessible safety showers.

RESPIRATORY PROTECTION No respiratory protection is required under normal

conditions.

INGESTION PROTECTION Wash before eating, drinking or smoking. Observe

the rules of hygiene.



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES PHYSICAL FORM Paste White COLOUR **ODOUR** Faint epoxy Hq N/A **BOILING POINT** No data **MELTING POINT** No data **FLASH POINT** > 100°C **FLAMMABILITY** 4 - Minimal **VAPOUR PRESSURE** No data **SPECIFIC GRAVITY** 2.2 **SOLUBILITY IN WATER** None **SECTION 10 - STABILITY AND REACTIVITY CHEMICAL STABILITY** Stable **CONDITIONS TO AVOID** Excessive heating over long periods of time degrades the product. **INCOMPATIBLE MATERIALS Amines** HAZARDOUS DECOMPOSITION PRODUCTS None **SECTION 11 - TOXICOLOGICAL PROPERTIES ACUTE ORAL TOXICITY (LD50, RAT)** > 2000 mg / kg **ACUTE DERMAL TOXICITY (LD50, RABBIT)** > 2000 mg / kg**ACUTE INHALATION TOXICITY (LC50, RAT)** Vapours are unlikely due to physical properties. **EYE AND SKIN CONTACT** Eye and skin irritant. Repeated exposure may cause skin sensitisation. **CARCINOGENICITY** Not a known carcinogen. **SECTION 12 - ECOLOGICAL INFORMATION** Material is expected to cause long term adverse effects in the aquatic environment.



SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL Use a reputable waste disposal contractor. Waste

disposal measures must comply with all Local and

National By-laws.

SECTION 14 - TRANSPORT INFORMATION

UN NUMBER 3082

IMO SHIPPING NAME Environmentally hazardous substance, N.O.S.

IMO CLASS AND DANGER GROUP Class 9, Danger Group III

IMO SUBSIDIARY RISK(S) None

SECTION 15 - REGULATORY INFORMATION

RISK (R) PHRASES R 36 / 38 - Irritating to eyes and skin.

R 43 - May cause sensitisation by skin contact.

R 51 / 53 - Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

SAFETY (S) PHRASES S 28 - After contact with skin, wash immediately with

plenty of water and soap.

S 37 / 39 - Wear suitable gloves and eye/face

protection.

S61 - Avoid release to the environment. Refer to

special instruction / material safety data sheet.

SECTION 16 - OTHER INFORMATION

Alert workers to this hazardous potential and ensure precautions are taken. In cases of any discomfort

always seek medical advice.

Flowcrete SA (Pty) Ltd is an RPM Company

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for error of omission or the consequences thereof.

Flowcrete (SA) Pty Ltd (2003/029560/07)
176 Voortrekker Street Jacobs Durban 4052
Tel: +27 31 461 3411 Fax: +27 31 461 3475
47 Forge Road Spartan Kempton Park Johannesburg 1620
Tel: +27 11 394 1980 Fax: +27 11 394 3003
Unit 5 55 Manhattan Street Boquinar Industrial Park Matroosfontein Cape Town 7490
Tel: +27 21 385 0653 Fax: 086 583 8358
Email: southafrica@flowcrete.com

Page 5 of 5 MSDS - Ivory 317 Hi Wear Epoxy